Dane aktualne na dzień: 31-10-2026 22:16

Link do produktu: https://sklep.firtech.pl/zawor-zwrotny-sterowany-pilotem-cpom6-zawory-w-a-i-b-otwarcie-0-4-bar-ng25-cetop-08-cpom6ddn-p-3881.html

Zawór zwrotny sterowany pilotem CPOM6 - zawory w A i B, otwarcie 0,4 bar (NG25, CETOP 08) CPOM6DDN

Dostępność	**Na zamówienie**
Numer katalogowy	**CPOM6DDN**
Kod producenta	**CPOM6DDN**

Opis produktu

Pilot operated check valves series CPOM are part of Parker's complete range of sandwich plate valves and ensure an easy configuration of conventional stack systems. Additionally they provides a very good price-performance ratio.Depending on the function required, one or two pilot operated check valves are arranged in the ports A and/or B. The free flow direction is always from the valve side to the manifold side.FunctionThe check valves open when flowing to the consumer side, where the opposing check valve is hydraulically-mechanically pilot operated simultaneously by a control spool, and thus the return flow is enabled from other consumer sides.Markets:• Industrial• Machine tools• Rubber & TireFeatures/Benefits• The valve bodies of the Parker Manapak valve series CPOM are made of steel• The valve poppet is precisely guided into the steel sleeve and ensures a good seal on the seat• When the valve poppet is open, the large cross-section allows high flow rates at low differential pressure• Different control ratios can be chosen with the NG06 and NG10 valves• Pre-opening for CPOM*HT to achieve smooth opening• Reliable operation in conventional stack systems• Very good price-perfomance ratio• Short delivery timeApplications:• Tire presses• Machine tool

Parametry techniczne

Parametr	Wartość
Rodzaj sterowania	Ciśnienie hydrauliczne
Materiał korpusu	Stal
Ciśnienie otwarcia	0.4 bar
Dywizja	Dywizja Systemów Zaworów Hydraulicznych Europa
Maks. natężenie przepływu	227 L/min
Maks. ciśnienie robocze	210 bar
Maks. ciśnienie robocze (bar)	210
Maks. temperatura pracy	60 °C
Min. temperatura pracy	-20 °C
Typ montażu	Płyta pośrednia (sandwich)
Stosunek ciśnienia otwarcia	1:3
Typ działania	Pilotowe (sterowanie wstępne)
Rodzaj grzybka	A, B

Przyłącze	NG25, CETOP 08
Seria produktu	Zawór zwrotny
Materiał uszczelnień	NBR
Waga	9.5 kg

Dokumenty

Literatura i materiały referencyjne

- KATALOG - Zawór zwrotny sterowany pilotem, seria CPOM

Prezentacje i filmy instruktażowe

- FILM O PRODUKCIE - Zawory zwrotne